3M 1342001



Details

- 6 ft. (1.8m) double-leg 100% tie-off lanyard
- Lightweight user friendly design
- PVC shock pack with protected label
- Abrasion resistant polyester webbing
- Energy absorbing design limits fall arrest forces
- User friendly self locking snap hooks at each end
- Impact indicator

6 ft. (1.8m) web double-leg 100% tie-off with snap hooks at each end.

Our PRO[™] Pack shock absorbing lanyards provide high quality compliance at an economical price and are trusted by workers. They feature durable webbing and plated alloy steel hardware for strength and corrosion resistance. PRO[™] Pack lanyards feature a controlled tearing action when subjected to a fall, reducing the forces imposed on the user to safe levels and stopping the fall. In addition, PRO[™] lanyards are lightweight and provide added comfort and safety. Various styles, lengths and hooks options are available to suit your specific jobsite needs.

Specifications

Anchor Connector Type	Snap Hook
Anchor Hook Material	Zinc Plated Steel
Brand	PRO™ Pack
Case Quantity	1
Color	Red
Energy Absorber Class	6 ft (1.8 m) Free Fall/MAAF 900 lbs. (4 kN)
Harness Connection Hook Material	Zinc Plated Steel
Harness Connector Type	Snap Hook
iSafe Equipped	No
Lanyard Material	Polyester Web
Lanyard Type	Fixed
Leg Count	Double-Leg 100% Tie-Off
Length	6 Feet
Product Series	PRO™ Pack
Product Type	100% Tie-Off Shock Absorbing Lanyard
Recommended Industry	Construction, General Industrial, Mining, Oil & Gas
Standards/Approvals	ANSI A10.32, OSHA 1910.66, OSHA 1926.502
Weight	3.2 lb.
Weight Capacity	130-310 lbs. (59-141kg)