

3M 2103143



Details

- Installs onto 3 in. to 8 in. wide I-beam flange (7.6-20.3cm) up to 11/16" thick (1.7cm)
- Complete hands-free horizontal mobility
- Ideal for use with self retracting lifeline
- Easy to use dual adjustment dials
- High strength steel construction
- Extremely rugged and corrosion resistant
- Rotating D-ring tie-off point is fixed in center
- Double-shielded wheel bearings
- Built-in guards protect wheels

Our anchorage connectors are built from top quality materials guaranteeing high strength and durability to stand up to the toughest environments. Anchorage connectors are the unsung heroes of most fall protection systems, often overlooked but critical components because they securely attach your system to the anchorage. Your choice of anchor depends on the type of work being done. Anchorages are sold by what they connect to (general/all purpose, steel, concrete, roof or specialty), whether they are fixed or mobile, and whether they are permanent or portable. They all must provide a secure point of attachment for a complete personal fall arrest system, and must be capable of supporting a load of 5,000 lbs. (22kN) or of meeting OSHA's criteria of a 2-to-1 safety factor.

Specifications

Attachment Type	Clamp
Case Quantity	1
Color	Yellow Zinc
Fits Ibeam Flange Width	76 - 203mm
For Use With	I-Beams
Install Type	Reusable
iSafe Equipped	Yes
Product Type	Beam Trolley
Recommended Industry	Construction, General Industrial, Mining, Oil & Gas, Transportation, Utilities, Wind Energy
Standards/Approvals	ANSI Z359.1, OSHA 1910.66, OSHA 1926.502
Weight	14 lb.
Weight Capacity	310 lbs. (141 kg) ANSI / 420 lbs. (190 kg) OSHA